

# **BLF 2550 Backing Layer Film**

## **DESCRIPTION**

BLF 2550 Backing Layer Film is a multilayer film for use as an external barrier layer in transdermal patches. It is a soft, flexible film with excellent barrier properties that help keep oxygen, moisture and other contaminants from penetrating the film structure.

### **CHARACTERISTICS**

- · Excellent oxygen, moisture and chemical barrier
- Excellent adhesion to nonwoven and polymer substrates
- Corona treated
- Printable
- Compatible with adhesive or extrusion lamination
- 3 mil. thickness
- Available in 6 in. to 80 in. widths

#### **FDA STATUS**

Manufactured with materials compliant with FDA regulations.

#### **COMPLIANCE**

Please visit transcendia.com/compliance for more compliance information.

#### **TECHNICAL DATA**

PROPERTIES		UNIT OF MEASURE	TYPICAL VALUES	TEST METHOD
Thickness		mil.	3	TTM 101384
Yield		in.²/lb.	9350	TTM 101257
Heat Seal, Out-In	MD	lb./in	4.79	TTM 101260
Heat Seal, Out-In	TD	lb./in	4.07	TTM 101260
OTR @23°C		cc/100in.2/day	.663	TTM 101558
WVTR @38°C and 90% RH		g/100in.²/day	.377	ASTM F1249
Ultimate Tensile Strength	MD	psi	3916	TTM 101305
Ultimate Tensile Strength	TD	psi	2799	TTM 101305
Ultimate Elongation	MD	%	441	TTM 101305
Ultimate Elongation	TD	%	593	TTM 101305

<sup>\*</sup>All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.