

ULTRA BLOCKOUT PROPRINT®

DESCRIPTION

Ultra Blockout ProPrint is a white, opaque substrate with blackout characteristics for two-side printed indoor and outdoor banners and signage.

CHARACTERISTICS

- Ultra high opacity that prevents ghosting from opposite sides
- Corona treated on both sides for dual side printing
- Good layflat characteristics
- Exceptional tear resistance
- Suitable for UV lithography, screen, flexo, UV digital and gravure printing methods
- Outdoor life expectancy is one year
- Exceptional dimensional stability
- Good toughness & impact strength

FDA STATUS

Manufactured with materials compliant with FDA regulations

COMPLIANCE

Please visit transcendia.com/compliance for more compliance information.

TECHNICAL DATA

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUES	TEST METHOD
Thickness	mil.	8	-
Yield	in ² /lb.	3,777	TM 101257
Tensile Strength @ Break, MD	psi	4,000	TM 101305
Tensile Strength @ Break, TD	psi	3,000	TM 101305
Tensile Modulus, 1% Secant, MD	psi	165,000	TM 101753
Tensile Modulus, 1% Secant, TD	psi	155,000	TM 101753
Opacity		>99	TM 101756

*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

CORPORATE HEADQUARTERS

9201 W. Belmont Avenue | Franklin Park, IL 60131
 USA 800.745.5802 | 847.678.1800 main | 847.233.0199 fax
 CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax
[TRANSCENDIA.COM](https://transcendia.com)